

(In compliance with EC/1907/2006 Article 31 and Annex II)

Revision Date: 30/10/2012

Revision Number: 0

Material/Trade Name: PALETTE TONER – VANADIUM YELLOW

1 – Identification of Substance/Mixture and of the Company/Undertaking

Material/Trade Name : Palette Toner – Vanadium Yellow
Material type : Photographic process reagent
Company : Jay House Ltd
Address : 6B Park Lane Industrial Estate
Park Lane
Corsham
SN13 9LG
Telephone : 01249 714555
Fax : 01249 714999
Internet : info@fotospeed.com

2 – Hazards Identification

Classification of the substance or mixture

According to Regulation (EC) No.1272/2008

Acute Toxic (Category 2) H330 Fatal if inhaled

According to European Directive 67/548/EEC as amended

T; Toxic
R23 Toxic by inhalation

3 – Composition/Information on Ingredients

CAS No.	EC No.	Index No.	Classification	Concentration
Hydrochloric Acid				
7647-01-0	231-595-7	017-002-01-X	Skin Corr. 1B, STOT SE 3 H314, H335 C; R34, Xi; R37	<4.4% w/w
Ammonium metavanadate				
7803-55-6	232-261-3	-	Acute Tox. 3, Acute Tox. 2, Eye Irrit. 2, STOT SE 3, Skin Irrit. 2 H301, H330, H319, H335, H315 T+; R25, T; R26, Xi; 36/37/38	2.5% w/w

4 - First-aid Measures

Inhalation:

Remove to fresh air and rest. If recovery is not rapid call for prompt medical attention. Show this safety data sheet to medical personnel.

Eyes

Irrigate with water for at least 15 minutes. Take care not to wash chemical from one eye to another. If irritation persists, obtain medical attention.

Skin

Remove contaminated clothing. Wash with soap/cleanser and rinse with plenty of water. If irritation persists, obtain medical attention.

Ingestion

Do NOT induce vomiting. Give plenty of water to drink. If feeling unwell seek prompt medical attention.

(In compliance with EC/1907/2006 Article 31 and Annex II)

Revision Date: 30/10/2012

Revision Number: 0

Material/Trade Name: PALETTE TONER – VANADIUM YELLOW

5 - Fire-fighting Measures

Suitable Extinguishers

Use media such as alcohol/aqueous foam, dry chemical, or carbon dioxide or water spray/fog which are suitable and appropriate for any surrounding fire.

Unsuitable Extinguishers

None.

Hazardous Decomposition

Hydrogen chloride gas, nitrogen oxides (NO_x), Sulphur oxides, Borane/boron oxides, Vanadium/vanadium oxides

Special Procedures/information for fire-fighters

Do not breathe decomposition products and fumes. Use approved self-contained breathing apparatus. Wear fire retardant clothing. Use water spray to cool containers. Prevent runoff from fire control from entering waterways. Large fires should only be dealt with by trained personnel.

6 - Accidental Release Measures

Personal Protection and Precautions

Use suitable personal protective equipment (refer to Section 8 for details). Avoid breathing vapours. Ensure adequate ventilation.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains or watercourses.

Containment, Cleaning up and Disposal Considerations

Absorb in inert material such as sand or non-combustible absorbent granules

Scoop up and place in plastic container to await transfer

Refer to Section 13 for further information regarding disposal.

7 - Handling and Storage

Handling

Avoid inhalation of vapour or mist.

Storage

Store in cool place. Keep container tightly closed in a dry and well-ventilated place.

8 - Exposure Controls/Personal Protection

Occupational Exposure Limit: 8 mg/m³ 8hrTWA WEL Hydrochloric Acid

Respiratory Protection

Use in well ventilated areas. Use mechanical ventilation if possible.

Hand Protection

Wear polythene, PVC or nitrile gloves to Standard EN 374 (breakthrough time for total immersion in excess of 8 hours).

Eye Protection

Wear suitable eye protection such as safety glasses or goggles to Standard BS EN 166 if splash or eye contact likely.

Skin Protection

Wear suitable overalls or apron and change if contaminated. After contact with skin wash off immediately. Wash hands before breaks and immediately after using the product.

9 - Physical & Chemical Properties

Appearance : Liquid

Odour : None

pH : n/e

Boiling point/range : n/e

Melting point/range : n/e

Flash point : n/e

Flammability : NON FLAMMABLE

Autoflammability : n/e

Explosive properties : n/e

Oxidising properties : None

Vapour pressure : n/e

Relative density : n/e

Solubility : Miscible in water

Partition Coefficient : n/e

Vapour Density : n/e

Viscosity : n/e

Evaporation rate : n/e

(n/e = not established)

(In compliance with EC/1907/2006 Article 31 and Annex II)

Revision Date: 30/10/2012

Revision Number: 0

Material/Trade Name: PALETTE TONER – VANADIUM YELLOW

10 - Stability and Reactivity

Chemical Stability

Stable at normal temperatures and under recommended storage conditions.

Conditions to Avoid

Extreme temperature and direct sunlight.

Materials to Avoid

Strong oxidizing agents, Water, Bases, Amines, Alkali metals, Metals, permanganates, e.g. potassium permanganate, Fluorine, metal acetylides, hexalithium disilicide.

Hazardous Decomposition Products

No hazardous decomposition products when stored and handled correctly.

11 - Toxicological Information

Acute toxicity

Toxic by inhalation. Ammonium Metavanadate;

LC₅₀ Inhalation, rat (acute lethal effects) from vapours >0.5, ≤2mg/litre/4h

Skin corrosion/irritation

Not expected to cause any acute skin corrosion or irritation at concentrations present in product

Serious eye damage/eye irritation

Not expected to cause any acute eye damage or irritation at levels present in product; low level transient eye irritation may be possible following exposure

Respiratory or skin sensitisation

Not expected to have sensitisation potential

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No components of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Inhalation - May cause respiratory irritation.

Potential health effects

Inhalation May be fatal if inhaled. Causes respiratory tract irritation.

Ingestion May be harmful if ingested in quantity.

Skin Repeated exposure may cause skin dryness or cracking.

Eyes May cause transient eye irritation

Signs and Symptoms of Exposure

Burning sensation, Cough, wheezing, laryngitis, Shortness of breath, spasm, inflammation and oedema of the larynx, spasm, inflammation and oedema of the bronchi, pneumonitis, pulmonary oedema, Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin.

(In compliance with EC/1907/2006 Article 31 and Annex II)

Revision Date: 30/10/2012

Revision Number: 0

Material/Trade Name: PALETTE TONER – VANADIUM YELLOW

12 - Ecological Information

Toxicity

Not expected to be harmful to aquatic life.

Persistence and degradability

No data available.

Mobility in soil

No data available.

PBT and vPvB assessment

No data available.

Bioaccumulative potential

No data available.

Other adverse effects

No data available.

13 -Disposal Considerations

Product

Material is classified as hazardous waste under the Hazardous Waste Regulations 2005 as amended). Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14 -Transport Information

ADR/RID

Not classified as hazardous for transport

IMDG

Not classified as hazardous for transport

Marine pollutant:

No

IATA

Not classified as hazardous for transport

15 - Regulatory Information

Label Elements

Pictogram



Signal Word

Danger

Hazard Statement(s)

H330 Fatal if inhaled

Precautionary statement(s)

P304 + P340 If inhaled: remove victim to fresh air and keep at rest in position comfortable for breathing

Other Regulations

Health & Safety at Work etc. Act 1974

Control of Substances Hazardous to Health Regulations 2002 (as amended)

Chemicals (Hazard Information and Packaging for Supply) Regulations 2009

Classification, Labelling and Packaging of Substances and Mixtures Regulations 2008 (as amended)

EH40/2005 Workplace Exposure Limits (as amended)

Environmental Protection Act 1990

Hazardous Waste Regulations 2005 (as amended)

Revision Date: 30/10/2012**Revision Number:** 0**Material/Trade Name:** PALETTE TONER – VANADIUM YELLOW

16 - Other Information**Text of H-code(s) and R-phrase(s) mentioned in Section 3**

H335	May cause respiratory irritation
H314	Causes severe burns and eye damage
H301	Toxic if swallowed
H330	Fatal if inhaled
H319	Causes serious eye irritation
H315	Causes skin irritation
R25	Toxic if swallowed
R26	Very toxic by inhalation
R36/37/38	Irritating to eyes, respiratory system and skin.

Recommended restrictions on use

Use in accordance with manufacturer's technical instructions.

Revision History

First Issue

Further Information

The information in this Safety Data Sheet should be provided to all who will use, handle, store, transport or otherwise be exposed to this product. This information has been prepared for the guidance of plant engineering, operations, management and for people working with or handling these products. This information is believed to be reliable and updated at Revision Date, and represents the best information currently available and known by Jay House Ltd. (Jay House). However, Jay House makes no guarantee or warranty, express or implied, with respect to such information and we assume no liability resulting from its use. The information related herein is based on proper handling and anticipated uses and is for the material without chemical additions or alterations. Users should make their own investigations to determine the suitability of the information for their particular purposes. It is the responsibility of the user to undertake a suitable risk assessment/COSHH assessment prior to using this material.